


## MW921 InSb Hall Element

Ultra High-sensitivity InSb Hall element

Thin-type SIP Package

Shipped in Bulk by Pack (500Pcs devices per pack)

### Dimensional Drawing (Unit MM)



### Absolute Maximum Rating

Operating Temperature Range -40°C ~ 110°C  
Storage Temperature Range -40°C ~ 125°C  
Maximum Input Current  $I_{cmax}$  [mA] 10mA

### Electrical Characteristic ( RT=25°C )

Copy Right Reserved

JZWI-DS-010 Version 1.4

Matrixopto.Co.,Ltd is the owner of the trademarks used in this document, which has the exclusive right to prevent any third parties not having the owner's consent from using in the course of trade identical or similar signs for goods or services where such use would result in a likelihood of confusion.

Table 1. Electrical Characteristics of MW921

| Item                      | Symbol          | Test Condi.  | Min. | Typ. | Max. | Unit                |
|---------------------------|-----------------|--|------|------|------|---------------------|
| Hall Voltage              | $V_H$           | $B = 50\text{mT}, V_C = 1\text{V}$<br>$T_a = \text{RT}$                              | 168  |      | 320  | mV                  |
| Input Resistance          | $R_{in}$        | $B = 0\text{mT}, I_C = 0.1\text{mA}$<br>$T_a = \text{RT}$                            | 240  |      | 550  | $\Omega$            |
| Output Resistance         | $R_{out}$       | $B = 0\text{mT}, I_C = 0.1\text{mA}$<br>$T_a = \text{RT}$                            | 240  |      | 550  | $\Omega$            |
| Offset Voltage            | $V_{os}$        | $B = 0\text{mT}, V_C = 1\text{V}$<br>$T_a = \text{RT}$                               | -7   |      | +7   | mV                  |
| Temp. Coeffi. of $V_H$    | $ \alpha V_H $  | $B = 50\text{mT}, I_C = 1\text{mA}$<br>$T_a = 0^\circ\text{C} \sim 40^\circ\text{C}$ |      | 1.8  |      | %/ $^\circ\text{C}$ |
| Temp. Coeffi. of $R_{in}$ | $\alpha R_{in}$ | $B = 50\text{mT}, I_C = 5\text{mA}$<br>$T_a = 0^\circ\text{C} \sim 40^\circ\text{C}$ |      | -1.8 |      | %/ $^\circ\text{C}$ |
| Dielectric strength       |                 | 100V D.C   | 1.0  |      |      | M $\Omega$          |

- $V_H = V_{H-M} - V_{os}$  in which  $V_{H-M}$  is the Output Hall Voltage,  $V_H$  is the Hall Voltage and  $V_{os}$  is the offset Voltage under the identical electrical stimuli.
- $\alpha V_H = \frac{1}{V_H(T_1)} \times \frac{V_H(T_3) - V_H(T_2)}{(T_3 - T_2)} \times 100$
- $\alpha R_{in} = \frac{1}{R_{in}(T_1)} \times \frac{R_{in}(T_3) - R_{in}(T_2)}{(T_3 - T_2)} \times 100$        $T_1 = 20^\circ\text{C}, T_2 = 0^\circ\text{C}, T_3 = 40^\circ\text{C}$

## Classification of Output Hall Voltage ( $V_H$ )

Table 2. Classification of Hall Voltage

| Rank | $V_H$ [mV] | Conditions       |
|------|------------|------------------|
| C    | 168 ~ 204  | B=50mT, $V_C=1V$ |
| D    | 196 ~ 236  |                  |
| E    | 228 ~ 274  |                  |
| F    | 266 ~ 320  |                  |

## Characteristic Curves




Figure 1. Input resistance  $R_{in}$  as a function of ambient temperature  $T_a$ .




Figure 2. Hall voltage  $V_H$  as a function of magnetic flux density  $B$ .




Figure 3. Hall voltage  $V_H$  as a function of ambient temperature  $T_a$ .




Figure 4. Hall voltage  $V_H$  as a function of electrical stimuli  $I_c/V_c$ .




Figure 5. Offset voltage  $V_{os}$  as a function of electrical stimuli  $I_c/V_c$ .

## Precautions for ESD

This product is the device that is sensitive to ESD (Electrostatic Discharge). Handling Hall Elements with the ESD-Caution mark under the environment in which

- Static electrical charge is unlikely to arise. (Ex; Relative Humidity; over 40%RH).
- Wearing the antistatic suit and wristband when handling the devices.
- Implementing measures against ESD as for containers that directly touch the devices.

## Precautions for Storage

- Products should be stored at an appropriate temperature and humidity (5 to 35°C, 40 to 60%RH) after the unsealing of MBB. **Using self-sealer is highly recommended.** Keeping products away from chlorine and corrosive gas.
- **For storage longer than 2 years**, it is recommended to store in nitrogen atmosphere with MBB sealed. Oxygen and H<sub>2</sub>O of atmosphere oxidizes leads of products and lead solder ability get worse.

## Precautions for Safety

- Do not alter the form of this product into a gas, powder or liquid through burning, crushing or chemical processing.
- Observe laws and company regulations when discarding this product.